

VR2 SERIES HEAVY DUTY ELECTRIC HOT TOP RANGE



- VR2** Standard Oven
- VR2C** Convection Oven

STANDARD FEATURES

- Stainless steel front, sides, stub back and front top ledge.
- 6" adjustable stainless steel legs.
- Three 5 KW cast iron thrift plates, 12"w x 24"d each.
- One thermostat control per hot top, adjusts from 340° to 800°F.
- Porcelain on steel baffled grease drawer and warming drawer under range top.
- 2½" fiberglass insulation in sides, top, back and bottom. 2" in door.
- Requires 208V or 240V, 1 or 3 phase power supply.
- **Standard oven (VR2):** 6.7 KW input. Top and bottom solid sheath heating elements with independent element controls. One oven rack with two rack positions. Thermostat with cycling light adjusts from 155° to 550°F. Oven interior measures 23½"w x 13"h x 31½"d.
- **Convection oven (VR2C):** 7 KW input. Six side mounted solid sheath heating elements. Three oven racks with five rack positions. Thermostat with cycling light adjusts from 200° to 500°F. ¼ H.P. blower-motor. Oven interior measures 19¼"w x 14½"h x 27"d.
- One year limited parts and labor warranty.

OPTIONS

- Without legs for masonry base - 31" working height.
- Marine features (contact factory).
- Export voltages.
- 480V, 60 Hz, 3 phase.
- Second year extended limited parts and labor warranty.

ACCESSORIES

- Additional oven racks.
- Set of four 5" diameter casters, (2 locking).
- 35" high double deck high shelf.
- VB73 elevated broiler, rated at 6 KW input.



SPECIFICATIONS:

Heavy duty electric hot top range, with oven, Vulcan-Hart Model No. VR2. Stainless steel front, sides, stub back and front top ledge. 6" adjustable stainless steel legs. Three 5 KW cast iron hot tops. One thermostat control per hot top adjusts from 340° to 800°F. Porcelain on steel baffled grease drawer and warming drawer under range top. 2½" fiberglass insulation in sides, top, back and bottom, with 2" in door. Requires 208 or 240 volt, 1 or 3 phase.

Exterior dimensions: 36"w x 38¼"d x 37"h.

NSF listed. UL listed to US and Canadian safety standards.

